

Balance of Performance SRO GT4 CARS PORTIMAO



BALANCE OF PERFORMANCE FOR SRO GT4 CARS:

Portimao

These balance of performance measures are the result of the tests, research, analysis and projections performed by SRO Ltd and are the sole property of SRO Ltd. Other series promoters, race organisers and national sporting authorities cannot use all or part of them without SRO Ltd's prior written consent. Any contravention will result in a legal action.



Balance of Performance SRO GT4 CARS PORTIMAO



Make	Model	Min Weight kg	BOP Ballast kg	Total weight	Ride Height Front	BOP extra mm	Ride Height Rear	BOP Extra mm	Comments
Aston Martin	AMR Vantage GT4	1445	+55	1500	93	+10	102	+0	MAP SRO 3 2020
ктм	X-BOW GT4 2018	1025	+90	1115	70	+40	192	+40	ECU 2018 BOP MAP, 2.26 pboost at 1010mb. REV Limit 6500 max Max CAMBER F2,3/R2,3
ктм	X-BOW GT4 2020	1025	+150	1175	70	+40	192	+20	ECU 2020 BOP MAP, 2,0 mbar pboost at 1010mb. REV Limit 7000 rpm max Max CAMBER 2,3F/2,3R
Mercedes	AMG GT4	1400	+55	1455	93	+10	96	+5	Power Level 2 MAP 2019 ECU BOP 2020
Porsche	718 Cayman GT4 CS MR	1301	+19	1320	101	+5	94	+0	ECU BOP MAP 2021

Remarks:

- Additional BOP Ballast must be installed according with art. 4.2 and art 4.3 of the GT4 Technical Regulations
- ECU BOP maps are saved in the dataloggers for scrutineering.
- GT4 Cars are only eligible if presented with GT4 homologation file and SRO GT4 Certificate
- SRO GT Bureau can use any parameter for BOP purposes and can change the BOP of any car at any moment during the event.
- Engine reference data (iA, Lambda, Fuel inj, Cam In/Out, airbox pressure) is the one collected during BOP tests and will be used for checks. If noted differently in comments the (e.g. iA, Lambda, Fuel inj, Cam In/Out, airbox pressure) is set as reference.
- Turbo cars without adaptable phoost need to add +15kg per 20 mbar ambient pressure delta under 1010mbar, this means + 15 kg at Patmo of 990mb,
- +30 kg at Patmo of 970 mbar and +45 kg at Patmo of 950 mbar